

Premium Sealer

# UZIN RESILIENT SEALER

Single component PUR sealer to protect resilient floor coverings

**MAIN APPLICATION FIELD:**

- ▶ care and protection of resilient floor coverings
- ▶ care and protection of natural and artificial stone

**PRODUCT BENEFITS/FEATURES:**

- ▶ PVC
- ▶ LVT / LVP (Luxury Vinyl Tile / Plank)
- ▶ CV
- ▶ Rubber floor coverings
- ▶ Natural and artificial stone
- ▶ Floor coverings PU-covered by the manufacturer



**PRODUCT BENEFITS/FEATURES:**

UZIN Resilient Sealer is a single component polyurethane sealer for the care and protection of resilient floor coverings as well as natural and artificial stone. Helps improve and extend the wear life of the floor. For interior use.

- ▶ hard wearing capability
- ▶ slip-resistant
- ▶ abrasion-resistant, long-term protection
- ▶ extends the wear life of the floor
- ▶ resistant against surface disinfectants
- ▶ fast drying



**TECHNICAL DATA:**

Packaging	plastic canister
Pack size	5 l
Shelf life	min. 5 years
Color, wet	transparent
Color, dry	transparent bright
Consumption	approx. 83 m <sup>2</sup>
Application temperature	18 - 25 °C
Working time	approx. 30 minutes*
Ready for foot traffic	after 5 hours*

\*At 21 °C and 65% relative humidity.



## SUBSTRATE PREPARATION:

- ▶ The floor must be structurally sound, solid, dry, clean and free of all contaminants such as grease, oil, paint and wax. Use UZIN Basic Cleaner for this.
- ▶ Use a wet cleaning machine to vacuum the water and residues after cleaning.
- ▶ Clean the floor 2 – 3 times with a microfiber mop and clear water. Surface must be dry before application.
- ▶ Protect all surfaces not to be coated with tape or other materials.

## APPLICATION:

1. Lightly shake the container for a short time before use.
2. Place UZIN Resilient Sealer into an oblong bucket, do not pour directly onto the floor covering.
3. Apply a undiluted coat onto the floor with a RZ Fine-fibre Mop in one direction.
4. Do not wipe. Allow surface to dry for 60 minutes and then, wash the mop.
5. Apply a second coat at 90 degrees to the first coat.
6. Floor can be walked on again after approx. 5 hours.
7. Do not place loads onto the floor for approx. 12 – 16 hours.

## IMPORTANT NOTES:

- ▶ A shelf life of 5 years when stored in moderately cool conditions, in the original packaging. Protect from frost. Carefully and tightly reseal opened containers and use the contents quickly. Allow containers to come to room temperature before use.
- ▶ Best applied between 18 - 25 °C and relative air humidity below 65%. Low temperatures and high air humidity lengthen the drying time. Whilst high temperatures and low air humidity shorten the working time.
- ▶ Regular maintenance with UZIN Resilient Care improves the surface appearance and prolongs the wear life.

## PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Non-flammable. Use of barrier cream and ventilation of the work area are recommended. Observe safety information on product label as well as safety data sheet.

## DISPOSAL:

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty, scraped and drip-free containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.