



# JOINT FILLER

Suitable for filling and sealing expansion joints, cracks, splits

## Storage:

Store in cool, dry conditions. Min. 12 months shelf-life in original, sealed containers. Protect containers from frost.

## Surface Preparation:

The surface must be dry, clean, and free from dust and grease. Prime very absorbent surfaces with the parquet joint material thinned with water (4 parts water : 1 part Pallmann Parquet Joint Filler). Deep joints should be filled using several layers.

## Application:

1. Cut off the nozzle tip at an angle and according to the desired joint width – screw onto the cartridge. Use only at temperatures above 18 – 25 °C and relative humidity below 65 %.
2. Apply the sealing compound evenly onto the surface using a suitable cartridge-gun. Distribute the compound in the joint and immediately smooth off.
3. Clean off fresh material immediately with water. Clean tools with water immediately after use.
4. The joint compound can, according to joint width, be sanded down, painted and sealed after approx. 24 hours\*.

\*Under normal conditions at 20 °C.



05.2015

Pallmann | A Brand of UFLOOR Systems  
D | PALLMANN GmbH  
Im Kreuz 6 | D-97076 Würzburg  
Telefon +49 (0)931 27964-0  
Telefax +49 (0)931 27964-50  
E-Mail [info@pallmann.net](mailto:info@pallmann.net)  
Internet [www.pallmann.net](http://www.pallmann.net)

NZ | AU UFLOOR Systems NZ Ltd.  
PO Box 426 Whangaparaoa 0943  
New Zealand  
Tel: +64 9 424 0366  
Fax: +64 9 424 0366 |  
E-mail: [ufloor-systems@xtra.co.nz](mailto:ufloor-systems@xtra.co.nz)



**PALLMANN**